



## Specifications Ledvance LED Panel Pendant 36W 3850lm - 830 Warm White | 120x30cm - UGR <19 - Dali Dimmable

[View Product](#)

### General Information

|                          |                                     |
|--------------------------|-------------------------------------|
| SKU                      | 236821                              |
| EAN                      | 4058075144644                       |
| Brand                    | Ledvance                            |
| Manufacturer Name        | PANEL D/I DALI 1200 36W/3000K UGR19 |
| Any Lamp all-in warranty | 5 Years                             |
| Average Lifetime (h)     | 80000                               |
| Series                   | Panel Led                           |

### Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 2x36               |
| Wattage                     | 36                 |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 830 Warm White     |
| Colour temperature (Kelvin) | 3000 Warm White    |
| Colour Rendering (Ra)       | 80-89              |
| Colour of Light             | White              |
| Light colour options        | Single Color       |
| Luminous Flux (Lumen)       | 3850               |

|                          |                   |
|--------------------------|-------------------|
| Luminous Efficacy (lm/W) | 100               |
| IP-rating                | IP20              |
| Impact Protection (IK)   | IK03 - 0.35 joule |
| Fixture Connection       | Terminal          |
| Driver Included          | Yes               |
| Power factor             | >0.90             |
| Product Type Category    | LED Panel         |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PMMA (Polymethyl methacrylate) |
| Operating Temperature | -20 to +45                     |
| Emergency Lighting    | No Emergency Unit              |
| Colour of the Fixture | White                          |
| Housing               | Aluminium                      |
| Colour of material    | White                          |

## Dimensions

|                |          |
|----------------|----------|
| LED panel size | 120x30cm |
| Length (mm)    | 1195     |
| Width (mm)     | 295      |
| Height (mm)    | 11       |

## Sensor Information

Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor



Up to **7 years warranty**

No Sensor



**Easy** return process