



Specifications Ledvance LED Panel  
Compact 33W 4320lm - 840 Cool White  
| 60x60cm - UGR <19 - Dali Dimmable

[View Product](#)

General Information

|                          |                                  |
|--------------------------|----------------------------------|
| SKU                      | 246942                           |
| EAN                      | 4099854015229                    |
| Brand                    | Ledvance                         |
| Manufacturer Name        | PL CMFT 600 P 33W 840 U19 DALIVR |
| Any Lamp all-in warranty | 5 Years                          |
| Average Lifetime (h)     | 70000                            |
| Series                   | PANEL COMFORT                    |

Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 4x18               |
| Wattage                     | 33                 |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 840 Cool White     |
| Colour temperature (Kelvin) | 4000 Cool White    |
| Colour Rendering (Ra)       | 80-89              |
| Colour of Light             | White              |
| Light colour options        | Single Color       |
| Including bulb              | Yes                |

|                          |                            |
|--------------------------|----------------------------|
| Luminous Flux (Lumen)    | 4320                       |
| Luminous Efficacy (lm/W) | 130                        |
| IP-rating                | IP40                       |
| Impact Protection (IK)   | IK02 - 0.20 joule          |
| Fixture Connection       | Screwless terminal, 5-Pole |
| Finish of Reflector      | Frosted                    |
| Power factor             | >0.90                      |
| Product Type Category    | LED Panel                  |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PS (Polystyrene)               |
| Operating Temperature | -10 to +50                     |
| Emergency Lighting    | No Emergency Unit              |
| Colour of the Fixture | White                          |
| Housing               | Aluminium                      |
| Colour of material    | White                          |

## Dimensions

|                |         |
|----------------|---------|
| LED panel size | 60x60cm |
| Length (mm)    | 595     |
| Width (mm)     | 595     |
| Height (mm)    | 32      |



Order from the **largest lighting specialist** in Europe



**Customised** quotation

## Sensor Information



Up to **7 years warranty**



**Easy** return process

|                |           |
|----------------|-----------|
| Type of sensor | No Sensor |
|----------------|-----------|